



FITTINGS FOR EMT

EMT AKSESUARLARI

ELECTROLINE EMT BORU RAKOR ve MUFLARI

EMT BORU RAKORLARI

EMT boruların, buat, pano, armatür ya da anahtar / priz kasalarında sonlandırılmasında kullanılır. ½" - 4" çap aralığında üretilirler. Vidalı ya da sıkmalı, zamak ya da çelik tipleri vardır. Kabloların sonlandırılmasında izolasyonun zarar görmemesi için, rakorlar izoleli olarak da tedarik edilir.

EL 121 Serisi:	Vidalı Tip, Zamak
EL 121 ST Serisi:	Vidalı Tip, Çelik
EL 121 A Serisi:	Vidalı Tip, Zamak, İzoleli
EL 121 ST A Serisi:	Vidalı Tip, Çelik, İzoleli
EL 21 Serisi:	Sıkmalı Tip, Zamak
EL 21 ST Serisi:	Sıkmalı Tip, Çelik
EL 21 A Serisi:	Sıkmalı Tip, Zamak, İzoleli
EL 21 ST A Serisi:	Sıkmalı Tip, Çelik, İzoleli



EMT BORU MUFLARI

EMT boruları birbirine eklemekte kullanılır. ½" - 4" çap aralığında üretilirler. Vidalı ya da sıkmalı, zamak ya da çelik tipleri vardır.

EL 122 Serisi:	Vidalı Tip, Zamak
EL 122 ST Serisi:	Vidalı Tip, Çelik
EL 22 Serisi:	Sıkmalı Tip, Zamak
EL 22 ST Serisi:	Sıkmalı Tip, Çelik




Electroline® EMT muf ve rakorlar UL Sertifika No:

½"-2"	E385459
2-½" - 4"	E385457

EMT Connectors and Couplings • EMT Muf ve Rakorlar

Set Screw Type Connector - Zinc Die Cast • Vidalı Tip Rakor - Zamak



½" - 2" E358459
2½" - 4" E358457

Features

- Set screw type connector
- Concrete tight when taped
- Assembled with a die cast locknut
- Available with insulated throat

Applications

- Connectors; use to join EMT to box or enclosure
- Couplings; use to join two lengths of EMT


Standard Material

- Zinc die cast

Catalog Number	Size	Unit Carton	Ship Case	Weight/ Case	Dimensions (in)		
					A	B	C
E-L 121	½"	50	500	35	1.16	.400	1.06
E-L 123	¾"	25	250	25	1.39	.400	1.30
E-L 125	1"	---	50	30	1.55	.520	1.52
E-L 127	1-¼"	---	25	8	1.93	.560	1.95
E-L 129	1-½"	---	25	10	2.28	.720	1.18
E-L 131	2"	---	20	11	2.50	.730	2.64
E-L 133-7	2-½"	---	12	10	3.08	.920	3.27
E-L 133-8	3"	---	12	12	3.37	1.050	3.91
E-L 133-9	3-½"	---	10	13	3.46	1.050	4.46
E-L 133-10	4"	---	6	9	3.75	1.050	4.99

½" - 1" 1 Screw 1¼" - 4" 2 Screw

Set Screw Type Connector with Insulated Throat - Zinc Die Cast • Vidalı Tip Rakor - İzoleli - Zamak




½" - 2" E358459
2½" - 4" E358457

Catalog Number	Size	Unit Carton	Ship Case	Weight/ Case	Dimensions (in)		
					A	B	C
E-L 121-A	½"	50	500	35	1.16	.400	1.06
E-L 123-A	¾"	25	250	25	1.39	.400	1.30
E-L 125-A	1"	50	200	30	1.55	.520	1.52
E-L 127-A	1-¼"	---	25	8	1.93	.560	1.95
E-L 129-A	1-½"	---	25	10	2.28	.720	1.18
E-L 131-A	2"	---	20	11	2.50	.730	2.64
E-L 133-7-A	2-½"	---	12	10	3.08	.920	3.27
E-L 133-8-A	3"	---	12	12	3.37	1.050	3.91
E-L 133-9-A	3-½"	---	10	13	3.46	1.050	4.46
E-L 133-10-A	4"	---	6	8	3.75	1.050	4.99

½" - 1" 1 Screw 1¼" - 4" 2 Screw

Set Screw Type Coupling - Zinc Die Cast • Vidalı Tip Muf - Zamak



½" - 2" E358459
2½" - 4" E358457
UL Standard: 514B
Fed.Spec. W-F-408E
NEMA: FB 1

Catalog Number	Size	Unit Carton	Ship Case	Weight/ Case	Dimensions (in)	
					A	B
E-L 122	½"	50	500	35	1.53	0.93
E-L 124	¾"	25	250	25	1.92	1.16
E-L 126	1"	50	200	28	1.00	1.44
E-L 128	1-¼"	---	25	8	2.52	1.84
E-L 130	1-½"	---	25	15	2.85	2.05
E-L 132	2"	---	20	11	3.41	2.51
E-L 134-7	2-½"	---	12	9	4.21	3.30
E-L 134-8	3"	---	12	12	4.67	4.01
E-L 134-9	3-½"	---	10	12	4.85	4.52
E-L 134-10	4"	---	6	10	5.47	5.01

½" - 1" 2 Screws 1¼" - 4" 4 Screws

EMT Connectors and Connector Couplings • EMT Muf ve Rakorlar

Compression Type Connector - Zinc Die Cast • Sıkmalı Tip Rakor - Zamak



Features


- Compression type connector
- Concrete tight
- Assembled with a die cast locknut
- Available with insulated throat

Applications

- Connectors; use to join EMT to box or enclosure
- Couplings; use to join two lengths of EMT


Standard Material

- Zinc die cast




Catalog Number	Size	Unit Carton	Ship Case	Weight/Case	Dimensions (in)		
					A	B	C
E-L 21	½"	50	500	50	1.26	1.26	.420
E-L 23	¾"	25	250	35	1.34	1.34	.420
E-L 25	1"	50	200	40	1.49	1.49	.525
E-L 27	1-¼"	---	25	10	1.67	1.67	.630
E-L 29	1-½"	---	20	11	1.87	1.87	.620
E-L 31	2"	---	15	12	2.01	2.01	.680
E-L 21-7	2-½"	---	12	13	2.63	2.63	.860
E-L 21-8	3"	---	12	16	2.77	2.77	1.01
E-L 21-9	3-½"	---	10	18	2.77	2.77	.94
E-L 21-10	4"	---	6	12	2.77	2.77	1.00

Compression Type Connector with Insulated Throat - Zinc Die Cast • Sıkmalı Tip Rakor - İzoleli - Zamak



Catalog Number	Size	Unit Carton	Ship Case	Weight/Case	Dimensions (in)		
					A	B	C
E-L 21-A	½"	50	200	50	1.26	1.26	.420
E-L 23-A	¾"	25	250	35	1.34	1.34	.420
E-L 25-A	1"	50	200	40	1.49	1.49	.525
E-L 27-A	1-¼"	---	25	10	1.67	1.67	.630
E-L 29-A	1-½"	---	20	11	1.87	1.87	.620
E-L 31-A	2"	---	15	12	2.01	2.01	.680
E-L 21-7-A	2-½"	---	12	13	2.63	2.63	.860
E-L 21-8-A	3"	---	12	16	2.77	2.77	1.01
E-L 21-9-A	3-½"	---	10	18	2.77	2.77	.94
E-L 21-10-A	4"	---	6	12	2.77	2.77	1.00


Compression Type Coupling - Zinc Die Cast • Sıkmalı Tip Muf - Zamak



Catalog Number	Size	Unit Carton	Ship Case	Weight/Case	Dimensions (in)	
					A	B
E-L 22	½"	50	500	60	1.50	1.10
E-L 24	¾"	25	250	48	1.62	1.31
E-L 26	1"	50	200	56	1.84	1.67
E-L 28	1-¼"	---	25	11	2.05	2.10
E-L 30	1-½"	---	20	14	2.47	2.30
E-L 32	2"	---	15	14	2.56	2.85
E-L 22-7	2-½"	---	12	16	3.29	3.70
E-L 22-8	3"	---	12	21	3.42	4.49
E-L 22-9	3-½"	---	10	22	3.51	5.06
E-L 22-10	4"	---	6	15	3.54	5.63

EMT Connectors and Couplings • EMT Muf ve Rakorlar

Set Screw Type Connector - Steel • Vidalı Tip Rakor - Çelik



½" - 2" E358459
2½" - 4" E358457

Features

- Set screw type connectors and couplings
- Concrete tight when taped
- Assembled with a steel locknut
- Available with insulated throat

Applications

- Connectors: Use to join EMT to box or enclosure
- Couplings: Use to join two lengths of EMT


Standard Material

- Steel
- Standard Finish
- Zinc plated

Catalog Number	Size	Unit Carton	Ship Case	Weight/ Case	Dimensions (in)		
					A	B	C
E-L 121 ST	½"	50	500	50	1.531	1.313	.438
E-L 123 ST	¾"	25	250	35	1.625	1.563	.469
E-L 125 ST	1"	50	200	46	2.250	1.938	.563
E-L 127 ST	1-¼"	—	25	10	2.500	2.250	.563
E-L 129 ST	1-½"	—	25	14	2.750	2.750	.563
E-L 131 ST	2"	—	20	16	3.313	3.563	.750
E-L 133 ST	2-½"	—	12	17	3.813	4.188	.938
E-L 135 ST	3"	—	12	22	3.938	4.688	.938
E-L 137 ST	3-½"	—	6	15	4.188	5.188	1.000
E-L 139 ST	4"	—	6	17	3.75	1.050	4.99

½" - 1" 1 Screw 1¼" - 4" 2 Screw

Set Screw Type Connector with Insulated Throat - Steel • Vidalı Tip Rakor - İzoleli - Çelik




½" - 2" E358459
2½" - 4" E358457

Catalog Number	Size	Unit Carton	Ship Case	Weight/ Case	Dimensions (in)		
					A	B	C
E-L 121 ST-A	½"	50	500	50	1.531	1.313	.438
E-L 123 ST-A	¾"	25	250	35	1.625	1.563	.469
E-L 125 ST-A	1"	50	200	46	2.250	1.938	.563
E-L 127 ST-A	1-¼"	—	25	10	2.500	2.250	.563
E-L 129 ST-A	1-½"	—	25	14	2.750	2.750	.563
E-L 131 ST-A	2"	—	20	16	3.313	3.563	.750
E-L 133 ST-A	2-½"	—	12	17	3.813	4.188	.938
E-L 135 ST-A	3"	—	12	22	3.938	4.688	.938
E-L 137 ST-A	3-½"	—	6	15	4.188	5.188	1.000
E-L 139 ST-A	4"	—	6	17	3.75	1.050	4.99

½" - 1" 1 Screw 1¼" - 4" 2 Screw

Set Screw Type Coupling - Steel • Vidalı Tip Muf - Çelik




½" - 2" E358459
2½" - 4" E358457
UL Standard: 514B
Fed. Spec. W-F-408E
NEMA: FB 1

Catalog Number	Size	Unit Carton	Ship Case	Weight/ Case	Dimensions (in)	
					A	B
E-L 122 ST	½"	50	500	50	1.750	.88
E-L 124 ST	¾"	25	250	38	2.125	1.06
E-L 126 ST	1"	10	100	24	2.500	1.31
E-L 128 ST	1-¼"	—	25	11	3.25	1.69
E-L 130 ST	1-½"	—	25	17	3.75	1.94
E-L 132 ST	2"	—	20	18	4.00	2.38
E-L 134 ST	2-½"	—	12	19	4.25	3.19
E-L 136 ST	3"	—	12	26	4.50	3.19
E-L 138 ST	3-½"	—	6	15	4.75	4.31
E-L 140 ST	4"	—	6	17	5.00	4.81

½" - 1" 2 Screws 1¼" - 4" 4 Screws

EMT Connectors and Couplings • EMT Muf ve Rakorlar

Compression Type Connector - Steel • Sıkmalı Tip Muf - Çelik



1/2" - 2" E358459
2 1/2" - 4" E358457
UL Standard: 514B
Fed. Spec. W-F-408E
NEMA: FB 1

Features

- Compression type connector and couplings
- Concrete tight
- Assembled with a steel locknut
- Available with insulated throat

Applications

- Connectors: Use to join EMT to box or enclosure
- Couplings: Use to join two lengths of EMT

Standard Material

- Steel

Standard Finish

- Zinc plated

Catalog Number	Size	Unit Carton	Ship Case	Weight/Case	Dimensions (in)		
					A	B	C
E-L 21 ST	1/2"	25	250	30	1.750	1.250	.406
E-L 23 ST	3/4"	25	250	43	1.813	1.563	.406
E-L 25 ST	1"	10	100	25	2.000	1.813	.406
E-L 27 ST	1-1/4"	---	25	12	2.750	2.188	.500
E-L 29 ST	1-1/2"	---	20	12	3.000	2.438	.500
E-L 31 ST	2"	---	15	15	3.188	2.938	.688
E-L 33 ST	2-1/2"	---	12	19	3.875	3.688	.750
E-L 35 ST	3"	---	6	15	4.375	4.313	.938
E-L 37 ST	3-1/2"	---	6	16	4.500	4.875	.938
E-L 39 ST	4"	---	6	21	4.750	5.375	.938


Compression Type Connector with Insulated Throat - Steel • Sıkmalı Tip Rakor - İzoleli - Çelik



1/2" - 2" E358459
2 1/2" - 4" E358457
UL Standard: 514B
Fed. Spec. W-F-408E
NEMA: FB 1

Catalog Number	Size	Unit Carton	Ship Case	Weight/Case	Dimensions (in)		
					A	B	C
E-L 21 ST-A	1/2"	25	250	30	1.750	1.250	.406
E-L 23 ST-A	3/4"	25	250	33	1.813	1.563	.406
E-L 25 ST-A	1"	10	100	28	2.000	1.813	.406
E-L 27 ST-A	1-1/4"	---	25	8	2.750	2.188	.500
E-L 29 ST-A	1-1/2"	---	20	9	3.000	2.438	.500
E-L 31 ST-A	2"	---	15	12	3.188	2.938	.688
E-L 33 ST-A	2-1/2"	---	12	19	3.875	3.688	.750
E-L 35 ST-A	3"	---	12	25	4.375	4.313	.938
E-L 37 ST-A	3-1/2"	---	6	15	4.500	4.875	.938
E-L 39 ST-A	4"	---	6	19	4.750	5.375	.938

Compression Type Coupling - Steel • Sıkmalı Tip Muf - Çelik




1/2" - 2" E358459
2 1/2" - 4" E358457
UL Standard: 514B
Fed. Spec. W-F-408E
NEMA: FB 1

Catalog Number	Size	Unit Carton	Ship Case	Weight/Case	Dimensions (in)	
					A	B
E-L 22 ST	1/2"	25	250	32	1.688	1.250
E-L 24 ST	3/4"	25	250	40	2.000	1.563
E-L 26 ST	1"	10	100	31	2.125	1.813
E-L 28 ST	1-1/4"	---	25	15	3.063	2.188
E-L 30 ST	1-1/2"	---	20	15	3.125	2.438
E-L 32 ST	2"	---	15	18	3.375	2.938
E-L 34 ST	2-1/2"	---	6	14	4.875	3.688
E-L 36 ST	3"	---	6	19	5.250	4.313
E-L 38 ST	3-1/2"	---	6	21	5.500	4.875
E-L 40 ST	4"	---	3	15	5.750	5.375

EMT 90° Connectors • EMT 90° Rakorlar

Compression Type - Zinc Die Cast • Sıkmalı Tip - Zamak



Features

- Concrete tight
- Exceptional wire pulling capability

Applications


- Indoor or outdoor use
- Use to connect EMT conduit to a steel outlet box or enclosure where a large radius is desired

Standard Material

- Zinc die cast

Catalog Number	Size	Unit Carton	Ship Case	Weight/ Case	Dimensions (in)		
					A	B	C
E-L 21-90-1	½"	25	250	50	1.75	.83	.52
E-L 23-90-2	¾"	20	200	52	1.86	.95	.52
E-L 25-90-3	1"	10	100	46	2.21	1.12	.67

Set Screw Type - EMT to EMT - Inside Corner - Zinc Die Cast • Vidalı Tip - Üstten Kapaklı - Zamak



Features

- Set screw assembly provides concrete tight connections when taped
- Removable cover facilitates wire pulling

Applications

- Dry location use
- Use to connect EMT conduit together on a 90° inside corner

Standard Material

- Zinc die cast


Catalog Number	Size	Unit Carton	Ship Case	Weight/ Case	Dimensions (in)	
					A	B
E-L 244-1	½"	10	100	20	1.81	1.00
E-L 244-2	¾"	5	50	15	2.00	1.25
E-L 244-3	1"	5	50	18	2.20	1.47

EMT 90° Rakorlar, buat, armatür, pano gibi sonlandırma noktasına paralel olarak çekilmiş ve büküm mesafesi olmayan, standart dirseklerin de uzun geldiği durumlarda, boruların sonlandırılmasında kolaylık sağlar.

L 244 serisi ise, boruların kısa ve keskin dönüşlerinde kullanılıp, üstten kapaklı olması sayesinde, ileride oluşabilecek değişikliklerde, kablolarla müdahale etme şansı verir. Dıştan dönüşlere nazaran içeriden dönüşler için tasarlanmıştır.

EMT 90° Pull Elbows • EMT 90° Kısa Dirsekler

Threaded Set Screw Type - EMT to Box - Zinc Die Cast • Dişli/Vidalı Tip - EMT/Buat Girişli - Zamak



Features

- EMT to box pull elbows
- Removable cover facilitates wire pulling
- Neoprene gasket

Applications


- Indoor or outdoor use
- Use to connect a run of EMT conduit to an outlet box or other metal enclosure
- Can be used with EMT indoors only

Standard Material

- Zinc die cast

Catalog Number	Size	Unit Carton	Ship Case	Weight/Case	Dimensions (in)			
					A	B	C	D
E-LG 143-1	½"	10	100	31	1.31	1.09	2.40	1.80
E-LG 143-2	¾"	5	50	18	1.47	1.29	2.66	2.14
E-LG 143-3	1"	—	25	21	2.80	1.60	3.66	3.16
E-LG 143-4	1-¼"	—	20	25	3.13	1.96	5.16	3.24

Set Screw Type - EMT to EMT - Zinc Die Cast • Vidalı Tip - EMT/EMT Girişli - Zamak



Features

- Corrosion resistant fabrication
- Removable cover facilitates wire pulling
- EMT to EMT pull elbows
- Removable cover facilitates wire pulling
- Neoprene gasket

Applications

- Dry location use
- Use to connect EMT conduit together on a 90° bend
- Use as a wire pulling elbow to facilitate wire pulling through a sharp bend in a run of EMT conduit

Standard Material


- Zinc die cast

Catalog Number	Size	Unit Carton	Ship Case	Weight/Case	Dimensions (in)			
					A	B	C	D
E-LG 144-1	½"	10	100	24	1.31	.94	2.50	1.78
E-LG 144-2	¾"	5	50	19	1.59	1.24	2.76	2.13
E-LG 144-3	1"	...	25	16	1.94	1.61	3.86	3.17
E-LG 144-4	1-¼"	...	20	20	2.26	2.00	4.56	3.25

EMT kısa dirsekler, kolon etrafından keskin dönüşlerde boruların eklenmesi ya da buat/panoda sonlandırılması için kullanılırlar. Kapaklı olmaları sayesinde, daha sonra bakım gerektiğinde kablolara kolaylıkla erişim sağlar.

EMT Offset Connectors • EMT Offset Rakorlar

Set Screw Type - EMT to Box - Zinc Die Cast • Vidalı Tip - EMT/Buat Bağlantısı İçin - Zamak



Features

- Concrete tight when taped

Applications


- Indoor or outdoor use
- Use to connect EMT conduit to a metal outlet box or enclosure where an offset is desired

Standard Material

- Zinc die cast

Catalog Number	Size	Unit Carton	Ship Case	Weight/ Case	Dimensions (in)		
					A	B	C
E-L 37-1	½"	10	100	12	2.10	.94	.52
E-L 37-2	¾"	10	100	19	3.00	1.16	.52
E-L 37-3	1"	10	100	25	3.16	1.42	.67

Compression Type - EMT to Box - Zinc Die Cast • Sıkmalı Tip - EMT/Buat Bağlantısı İçin - Zamak



Features

- Concrete tight

Applications

- Indoor or outdoor use
- Use to connect EMT conduit to a metal outlet box or enclosure where an offset is desired

Standard Material


- Zinc die cast

Catalog Number	Size	Unit Carton	Ship Case	Weight/ Case	Dimensions (in)		
					A	B	C
E-L 39-1	½"	20	200	26	2.13	1.00	.52
E-L 39-2	¾"	10	100	21	2.90	1.19	.75
E-L 39-3	1"	10	100	28	3.20	1.42	.75

Offset rakorlar, boru buat bağlantılarında gerekli olan "S" yükseltisi için tasarlanmıştır. Eğer borunun buata olan mesafesi büküm için yeterli değilse, sıkmalı ya da vidalı offset rakor sahada imalatı kolaylaştıracaktır. Buatların patlatmalı delikleri zeminden yüksekte olduğu için, offset rakorlar boruları kolay ve düzgün sonlandırmakta yardımcı olan bir aksesuardır.

EMT Straps • EMT Kroşeler

Snap-On Type - One Hole - Steel • Tek Kulak Kroşeler - Çelik



Catalog Number	Size	Unit Carton	Ship Case	Weight/ Case	Dimensions (in)	
					A	B
E-L 650	½"	100	1000	25	1.79	.57
E-L 651	¾"	100	1000	30	1.96	.62
E-L 652	1"	50	500	25	2.25	.75
E-L 653	1-¼"	25	250	20	2.85	.88
E-L 654	1-½"	10	100	12	3.16	.99
E-L 655	2"	10	100	16	3.93	1.10
E-L 606T*	2-½"	—	50	21	5.00	1.28
E-L 607T*	3"	—	25	13	5.55	1.28
E-L 608T*	3-½"	—	25	18	6.37	1.28
E-L 609T*	4"	---	25	20	6.87	1.28
E-L 610T*	5"	---	10	5	9.00	1.50
E-L 611T*	6"	---	10	6	10.35	1.50

* EMT and Rigid

2" üzerindeki kroşeler EMT ve Rijid için ayrıdır.

Features

- Snap-on type EMT strap with one hole
- Inverted rib for strength

Applications

- Support EMT conduit


Standard Material

- Steel

Standard Finish

- Zinc plated

Snap-On Type - Two Hole - Steel • Çift Kulak Kroşeler - Çelik



Catalog Number	Size	Unit Carton	Ship Case	Weight/ Case	Dimensions (in)	
					A	B
E-L 660-1	½"	50	500	10	2.20	.56
E-L 660-2	¾"	50	500	10	2.67	.62
E-L 660-3	1"	50	500	15	2.97	.68
E-L 660-4	1-¼"	20	200	12	3.67	.75
E-L 660-5	1-½"	20	200	16	4.22	.88
E-L 660-6	2"	—	50	7	4.91	1.00
E-L 660-7*	2-½"	—	25	6	5.91	1.00
E-L 660-8*	3"	—	25	7	6.71	1.00
E-L 660-9*	3-½"	—	25	8	7.51	1.00
E-L 660-10*	4"	—	25	7	8.31	1.00
E-L 660-11*	5"	—	10	5	10.60	1.25
E-L 660-12*	6"	—	10	6	11.85	1.28

* EMT and Rigid

2" üzerindeki kroşeler EMT ve Rijid için ayrıdır.

Features

- Snap-on type EMT strap with two holes

Applications

- Use to support EMT conduit where greater load bearing is required

Standard Material


- Steel

Standard Finish

- Zinc plated

Combination Couplings • Ara Bağlantılar

Screw In Type - EMT Compression to Flex - Zinc Die Cast
İçten Geçmeli - Sıkmalı - EMT/Spiral - Zamak



Features

- Screw in to compression type
- Combination coupling used to join flexible metal conduit to EMT

Applications


- Indoor use only
- Use to join EMT conduit to flexible metallic conduit
- Suitable for: 1/2" steel, steel reduced wall, and aluminum flexible metal conduit to EMT, 3/4"-1" flexible metal conduit to EMT

Standard Material

- Zinc die cast

Catalog Number	Size	Unit Carton	Ship Case	Weight/ Case	Dimensions (in)		
					A	B	C
E-L 49-1	1/2" - 1/2"	50	500	40	1.660	1.000	.723
E-L 49-2	3/4" - 3/4"	25	250	28	1.680	1.180	.931
E-L 49-3	1" - 1"	25	250	58	1.895	1.625	1.070

Compression Type EMT to Rigid - Steel • Sıkmalı Tip - EMT - IMC / Rijid - Çelik



UL standard 514B NEMA FB 1
Federal Spec A-A-50553

Features

- Internally threaded for Rigid/IMC conduit
- Compression type EMT
- Raintight

Applications

- Indoor use only
- Use to join Rigid/IMC conduit to EMT between 2 different raceways
- Coupling internally threaded for Rigid/IMC
- Compression type for EMT, concrete tight

Standard Material


- Steel

Standard Material

- Zinc plated

Catalog Number	Size	Unit Carton	Ship Case	Weight/ Case	Dimensions (in)	
					A	B
E-L ETR50	1/2"	20	200	31	1.1	1.57
E-L ETR75	3/4"	10	100	21	1.33	1.62
E-L ETR100	1"	10	100	30	1.63	1.82

EMT Insulating Bushings • EMT Entüller - Dıştan Geçmeli - Polietilen



Features

- Provides smooth, rounded surfaces at ends of raceways and avoids abrasion damage to cables

Applications

- Indoor use only
- Protects cables in communications and security systems against abrasion from edge of EMT

Standard Material

- Polyethelene
- Black / Clear Color Available

Catalog Number	Size	Unit Carton	Ship Case	Weight/ Case	Dimensions (in)	
					A	B
E-L TEN-050	1/2"	100	1000	5	.522	.570
E-L TEN-075	3/4"	100	1000	6	.538	.764
E-L TEN-100	1"	50	500	5	.614	.954
E-L TEN-125	1-1/4"	25	250	4	.620	1.26
E-L TEN-150	1-1/2"	25	250	5	.620	1.44
E-L TEN-200	2"	20	200	5	.619	1.86
E-L TEN-250	2-1/2"	—	25	1	1.12	2.34
E-L TEN-300	3"	—	25	2	1.19	2.78
E-L TEN-350	3-1/2"	—	25	2	1.22	3.27
E-L TEN-400	4"	—	25	2	1.22	3.71