


## Pull Elbows with Gasket • Contalı Kısa Dirsek

Rigid to Rigid • IMC/Rijid 90° Ek Parçası



### Features

- Rigid to Rigid
- Removable cover facilitates wire pulling
- Neoprene gasket

### Applications

- Indoor or outdoor use (Rigid only)
- Use as a wire pulling elbow to facilitate wire pulling through a sharp bend in a run of threaded Rigid or IMC conduit
- Can be used with EMT indoors only

### Standard Material


- Zinc die cast
- Neoprene gasket



| Catalog Number | Size   | Unit Carton | Ship Case | Weight/ Case | Dimensions (in) |      |      |      |
|----------------|--------|-------------|-----------|--------------|-----------------|------|------|------|
|                |        |             |           |              | A               | B    | C    | D    |
| E-LG 141-1     | 1/2"   | 10          | 100       | 28           | 1.31            | 1.09 | 2.50 | 1.78 |
| E-LG 141-2     | 3/4"   | 5           | 50        | 17           | 1.43            | 1.29 | 2.76 | 2.13 |
| E-LG 141-3     | 1"     | ---         | 25        | 16           | 1.95            | 1.59 | 3.86 | 3.17 |
| E-LG 141-4     | 1-1/4" | ---         | 20        | 18           | 2.26            | 1.97 | 4.56 | 3.25 |

## Pull Elbows with Gasket • Contalı Kısa Dirsek

Rigid to Box • IMC/Rijid 90° Contalı Rakor



### Features

- Rigid to box
- Removable cover facilitates wire pulling
- Neoprene gasket

### Applications

- Indoor or outdoor use (Rigid only)
- Use to connect a run of threaded Rigid or IMC conduit to an outlet box or other metal enclosure
- Can be used with EMT indoors only

### Standard Material

- Zinc die cast
- Neoprene gasket



| Catalog Number | Size   | Unit Carton | Ship Case | Weight/ Case | Dimensions (in) |      |      |      |
|----------------|--------|-------------|-----------|--------------|-----------------|------|------|------|
|                |        |             |           |              | A               | B    | C    | D    |
| E-LG 142-1     | 1/2"   | 10          | 100       | 31           | 1.31            | 1.09 | 2.40 | 1.80 |
| E-LG 142-2     | 3/4"   | 5           | 50        | 18           | 1.47            | 1.29 | 2.66 | 2.14 |
| E-LG 142-3     | 1"     | ---         | 25        | 21           | 2.80            | 1.60 | 3.66 | 3.16 |
| E-LG 142-4     | 1-1/4" | ---         | 20        | 25           | 3.13            | 1.96 | 5.16 | 3.24 |

LG 141 serisi kısa dirsekler, IMC/Rijid boruların, kolon ya da duvar köşesi gibi keskin dönüşlerde birbirlerine eklenmesinde kullanılır.

LG 142 serisi kısa dirsekler ise aynı durumlarda buat ya da panoya giriş için kullanılırlar.

Her iki model de contalı olduğu için, harici ortamlara uygun olup, kapaklı olmaları da gerektiğinde kablolarla müdahale edebilmeyi sağlar.