


Rigid Couplings • IMC/Rijid Muflar

Three Piece Type • 3 Parçalı (Erickson®) Tip

Die Cast Zinc / Malleable Iron / Steel • Zamak / PİK Döküm / Çelik



Features

- For threaded Rigid or IMC conduit

Applications

- Use as a threaded coupling between lengths of threaded Rigid or IMC conduit

Standard Material

- Malleable iron / Die cast zinc / Steel


Standard Finish

- Zinc plated

Catalog Number	Size	Unit Carton	Ship Case	Weight/ Case	Dimensions (in)	
					A	B
E-L 500	½"	20	200	40	1.43	1.36
E-L 501	¾"	10	100	30	1.63	1.58
E-L 502	1"	5	50	23	1.81	1.89
E-L 503	1-¼"	5	50	55	2.19	2.38
E-L 504	1-½"	3	30	44	2.31	2.83
E-L 505	2"	---	20	44	2.44	3.29
E-L 506	2-½"	---	10	37	2.52	4.03
E-L 507	3"	---	5	20	2.58	4.62
E-L 508	3-½"	---	5	29	2.65	5.35
E-L 509	4"	---	2	18	3.42	5.87

Offset Nipples • Offset Nipel

¾" Offset - Zinc Die Cast • ¾" Yükselti - Zamak



Features

- Enables easier direction change of conduit

Applications

- Indoor or outdoor use
- Use as an offset connector between two enclosures
- Offsets the axis of the raceways by ¾"

Standard Material

- Zinc die cast

Catalog Number	Size	Unit Carton	Ship Case	Weight/ Case	Dimensions (in)		
					A	B	C
E-L 376	½"	10	100	12	2.460	1.000	.750
E-L 377	¾"	10	100	16	2.560	1.220	.750
E-L 378	1"	10	100	22	2.560	1.525	.750
E-L 379	1-¼"	5	50	17	2.910	1.910	.750
E-L 380	1-½"	5	50	23	3.080	2.125	.750
E-L 381	2"	2	20	13	3.145	2.665	.750
E-L 382	2-½"	---	2	13	3.970	3.280	.750
E-L 383	3"	---	2	6	4.420	3.795	.750