


Rigid Couplings • Dişli Boru Ek Mufları

Tubular Threaded Type - Galvanized Steel • Galvanizli Çelik



Catalog Number	Size	Threads Per Inch	Ship Case	Weight / Case	Dimension (in)	
					A	B
E-TRC 1/2	1/2"	14	100	.12	1.63	1.563
E-TRC 3/4	3/4"	14	50	.17	1.64	1.625
E-TRC 1	1"	11-1/2	30	.29	1.97	2.000
E-TRC 1 1/4	1-1/4"	11-1/2	25	.38	2.03	2.063
E-TRC 1 1/2	1-1/2"	11-1/2	25	.53	2.06	2.063
E-TRC 2	2"	11-1/2	20	.70	2.13	2.125
E-TRC 2 1/2	2-1/2"	8	12	1.80	2.19	3.125
E-TRC 3	3"	8	8	2.26	3.31	3.250
E-TRC 3 1/2	3-1/2"	8	4	3.50	3.41	3.375
E-TRC 4	4"	8	4	3.13	3.52	3.500
E-TRC 5	5"	8	2	4.75	3.95	3.750
E-TRC 6	6"	8	1	7.65	4.25	4.000

Features

- NPSM thread type Applications
- Indoor or outdoor use
- Use to join and ensure proper alignment of threaded Rigid or IMC conduit

Standard Material

- Steel Standard Finish
- Zinc plated

Özellikler:

- NPT dişli
- Dahili ya da harici kullanıma uygun
- Dişli boruları birbirine eklemekte kullanılır

Malzeme

- Galvanizli Çelik



E468594

1/2"-4" meet UL 6 and ANSI C80.1
Federal Specification WW-C-563