

## PVC COATED FLEXIBLE METAL CONDUIT PVC KAPLI ÇELİK SPİRAL

- Material: PVC Coated Flexible Metal Conduit, Square Locked
- Certification: CE, GOST
- Operating Temperature: -40°C / +70°C
- Index of Protection: IP 65 (When used with listed liquidtight fittings)
- Colour: Black (Gray available upon request)

- Malzeme: PVC kaplı galvanizli çelik
- Sertifika: CE, GOST
- Çalışma Sıcaklığı: -40°C / +70°C
- Koruma Sınıfı: IP 65 (Electroline® liquidtight aksesuarlarla kullanıldığında)
- Renk: Siyah, (Gri istenirse siparişte bildiriniz.)

Catalog No. Katalog No.	Size / Ölçü (mm)	Inside Dia. İç Çap (mm)	Outside Dia. Dış Çap (mm)	Bending Ø Bükülme Ø (mm)	Roll Length Rulo Uzunluğu (mt.)
E-CTN-038	3/8"	12,20	16,00	45,00	50
E-CTN-050	1/2"	15,50	20,00	50,00	50
E-CTN-075	3/4"	20,50	26,00	70,00	50
E-CTN-100	1"	26,50	32,00	95,00	25
E-CTN-125	1-1/4"	34,50	40,00	110,00	25
E-CTN-150	1-1/2"	39,50	46,50	120,00	25
E-CTN-200	2"	50,50	57,00	140,00	25
E-CTN-250	2-1/2"	63,00	70,00	250,00	10
E-CTN-300	3"	75,00	87,00	300,00	10
E-CTN-400	4"	102,00	112,00	350,00	10



## STEEL BRAIDED FLEXIBLE METAL CONDUIT ÇELİK TEL ÖRGÜLÜ PVC KAPLI ÇELİK SPİRAL BORU

- Material: Steel Braided PVC Coated Flexible Metal Conduit, Square Locked
- Certification: CE, GOST
- Operating Temperature: -40°C / +70°C
- Index of Protection: IP 65 (When used with listed liquidtight fittings)

- Malzeme: Çelik Tel Örgülü PVC Kaplı Çelik Spiral Boru
- Sertifika: CE, GOST
- Çalışma Sıcaklığı: -40°C / +70°C
- Koruma Sınıfı: IP 65 (Electroline® liquidtight aksesuarlarla kullanıldığında)

Catalog No. Katalog No.	Size / Ölçü (mm)	Inside Dia. İç Çap (mm)	Outside Dia. Dış Çap (mm)	Bending Ø Bükülme Ø (mm)	Roll Length Rulo Uzunluğu (mt.)
E-BRD-050	1/2"	15,50	21,00	50,00	50
E-BRD-075	3/4"	20,50	28,00	60,00	50
E-BRD-100	1"	26,50	34,00	80,00	25
E-BRD-125	1-1/4"	34,50	44,00	110,00	25
E-BRD-150	1-1/2"	39,50	49,50	130,00	25
E-BRD-200	2"	50,50	58,00	150,00	25

