


## Conduit Bodies with Cover and Gasket Combination (EMT/IMC/RIGID) LB Type

### Conta ve Kapaklı Kondületler Dişli ve Vidalı Girişli, LB Tipi



#### Features

- Set screw and threaded LB type with cover and gasket
- Suitable for use in concrete
- NPT Tapered hubs
- NEMA FB1 rated for wet locations use with threaded rigid metal conduit only

#### Applications

- Provides access to conductors for pulling, splicing and maintenance

#### Standard Material

- Copper free aluminum die cast
- Steel screws


#### Standard Finish

- Powder coat

Catalog Number	Size	Wire Size		Unit Carton	Ship Case	Weight / Case	Dimensions (in)		
		Max. Number	Max. Size				A	B	C
E-LB-50-CG	1/2"	2	6 AWG	10	100	29	4.560	2.060	1.310
E-LB-75-CG	3/4"	2	6 AWG	10	50	23	5.090	2.430	1.540
E-LB-100-CG	1"	3	6 AWG	5	25	19	5.915	2.765	1.740
E-LB-125-CG	1-1/4"	3	2 AWG	2	10	14	7.894	3.665	2.490
E-LB-150-CG	1-1/2"	3	2 AWG	2	10	15	7.894	3.665	2.490
E-LB-200-CG	2"	3	2/0 AWG	1	5	14	10.134	4.275	3.100
E-LB-250-CG	2-1/2"	3	2/0 AWG	—	1	7	12.500	5.437	4.450
E-LB-300-CG	3"	3	4/0 AWG	—	1	7	12.500	5.657	4.450
E-LB-350-CG	3-1/2"	3	500 MCM	—	1	10	15.500	6.922	5.500
E-LB-400-CG	4"	3	500 MCM	—	1	10	15.500	6.922	5.500

## Combination (EMT/IMC/RIGID) C Type

### Dişli ve Vidalı Girişli, C Tipi



#### Features

- Set screw and threaded C type with cover and gasket
- Suitable for use in concrete
- NPT Tapered hubs
- NEMA FB1 rated for wet locations use with threaded rigid metal conduit only

#### Applications

- Provides access to conductors for pulling, splicing and maintenance

#### Standard Material

- Copper free aluminum die cast
- Steel screws

#### Standard Finish

- Powder coat

Catalog Number	Size	Wire Size		Unit Carton	Ship Case	Weight / Case	Dimensions (in)		
		Max. Number	Max. Size				A	B	C
E-C-50-CG	1/2"	2	6 AWG	5	100	30	4.720	1.370	1.330
E-C-75-CG	3/4"	2	6 AWG	5	50	21	5.570	1.625	1.540
E-C-100-CG	1"	3	6 AWG	5	25	25	6.460	1.900	1.740
E-C-125-CG	1-1/4"	3	2 AWG	5	25	15	8.528	2.770	2.490
E-C-150-CG	1-1/2"	3	2 AWG	5	10	17	8.528	2.770	2.490
E-C-200-CG	2"	3	2/0 AWG	1	5	13	10.831	3.335	3.100
E-C-250-CG	2-1/2"	3	4/0 AWG	—	1	6	13.00	4.063	5.709
E-C-300-CG	3"	3	250 MCM	—	1	6	12.50	4.682	5.506
E-C-350-CG	3-1/2"	3	350 MCM	—	1	8	15.50	5.452	6.171
E-C-400-CG	4"	4	350 MCM	—	1	8	15.50	5.452	6.171