


Combination (EMT/IMC/RIGID) LL Type
Dişli ve Vidalı Girişli, LL Tipi



Features

- Set screw and threaded LL type with cover and gasket
- Suitable for use in concrete
- NPT Tapered hubs
- NEMA FB1 rated for wet locations use with threaded rigid metal conduit only

Applications


- Provides access to conductors for pulling, splicing and maintenance

Standard Material

- Copper free aluminum die cast
- Steel screws Standard Finish
- Powder coat

Catalog Number	Size	Wire Size		Unit Carton	Ship Case	Weight / Case	Dimensions (in)		
		Max. Number	Max. Size				A	B	C
E-LL-50-CG	1/2"	2	6 AWG	10	100	36	4.295	1.310	2.060
E-LL-75-CG	3/4"	2	6 AWG	10	50	23	5.090	1.625	2.330
E-LL-100-CG	1"	3	6 AWG	5	25	18	5.915	1.900	2.650
E-LL-125-CG	1-1/4"	3	2 AWG	2	10	14	7.894	2.770	3.385
E-LL-150-CG	1-1/2"	3	2 AWG	2	10	16	7.894	2.770	3.385
E-LL-200-CG	2"	3	2/O AWG	1	5	14	10.134	3.335	3.810
E-LL-250-CG	2-1/2"	3	4/O AWG	---	1	6	12.500	5.437	4.450
E-LL-300-CG	3"	3	250 MCM	---	1	6	12.500	5.657	4.450
E-LL-350-CG	3-1/2"	3	350 MCM	---	1	8	15.500	6.922	5.500
E-LL-400-CG	4"	4	350 MCM	---	1	8	15.500	6.922	5.500

Combination (EMT/IMC/RIGID) LR Type
Dişli ve Vidalı Girişli, LR Tipi



Features

- Set screw and threaded LR type with cover and gasket
- Suitable for use in concrete
- NPT Tapered hubs
- NEMA FB1 rated for wet locations use with threaded rigid metal conduit only

Applications

- Provides access to conductors for pulling, splicing and maintenance

Standard Material

- Copper free aluminum die cast
- Steel screws

Standard Finish

- Powder coat

Catalog Number	Size	Wire Size		Unit Carton	Ship Case	Weight / Case	Dimensions (in)		
		Max. Number	Max. Size				A	B	C
E-LR-50-CG	1/2"	2	6 AWG	10	100	36	4.295	1.310	2.060
E-LR-75-CG	3/4"	2	6 AWG	10	50	28	5.090	1.625	2.330
E-LR-100-CG	1"	3	6 AWG	5	25	17	5.915	1.900	2.650
E-LR-125-CG	1-1/4"	3	2 AWG	2	10	15	7.894	2.770	3.385
E-LR-150-CG	1-1/2"	3	2 AWG	2	10	18	7.894	2.770	3.385
E-LR-200-CG	2"	3	2/O AWG	1	5	14	10.134	3.335	3.810
E-LR-250-CG	2-1/2"	3	4/O AWG	---	1	7	12.500	5.437	4.450
E-LR-300-CG	3"	3	250 MCM	---	1	7	12.500	5.657	4.450
E-LR-350-CG	3-1/2"	3	350 MCM	---	1	10	15.500	6.922	5.500
E-LR-400-CG	4"	4	350 MCM	---	1	10	15.500	6.922	5.500